

update @ elwet

ELWET AG
[SELATEC](#) | [ELWET](#) | [TELJET](#)
Electronic and Multimedia Solutions
Zugerstrasse 22 | CH-6314
Unterägeri | Fon +41 41 766 00 66
[Contact](#) | [Website](#)

PROTEK DEVICES PHS5xx/CA Series



A tiny but Mighty High Power TVS

ProTek Devices' PHS5xx/C series is a new state of the art family of TVS devices. The 500W series is offered in a DFN-2 highly thermal efficient package. They are designed for circuit protection in AC/DC power adapters, LED lighting clusters, smartphones and tablets, and more.

They boast unidirectional and bidirectional configuration options and a low clamping voltage. They are available in multiple operating voltages from 5V to 36V.


APPLICATIONS

- AC/DC Power Adapters
- LED Lighting Clusters
- Smart Phones and Tablets
- Portable Electronics
- Mother boards
- Electronic Controls

CLIQUE HERE FOR DATASHEET: [PHS5xx/CA](#)

Please contact us for inquiries, samples or technical requests.

COMCHIP CDBWL521-HF



Case 01005A

SMD Schottky Barrier Diode

FEATURES

- Ultra small SMD package
- Designed for mounting on small surface.
- Extremely thin package.
- Low stored charge.
- Majority carrier conduction.


MECHANICAL DATA

- Case: 01005 package, molded plastic.
- Polarity: Indicated by cathode band.
- Mounting position: Any

CLIQUE HERE FOR DATASHEET: [CDBWL521-HF](#)

Please contact us for inquiries, samples or technical requests.

FREQTECH – FT3B



Alternative to JAUCH VX3E – GEYER KXO-97
7.0 x 5.0 mm

FEATURES

- Frequency: 1.0 ~ 125.0MHz
- Dimension: 7.0 x 5.0 x 1.7 mm
- Frequency Tolerance @25°C: ±20~±100 ppm
- Storage temperature range: -40 to +85°C
- Aging: ±3 ppm /year max.

INFORMATION

- Short lead times

CLIQUE HERE FOR DATASHEET: [FT3B](#)

Please contact us for inquiries, samples or technical requests.

Since 57 years we are your partner for electronic components!